FL	EXIE	BLE FLAT CABLE (SAMF	PLE REQUEST / INQUIRY F	ORM)
Customer Name			Application		
Email Address	 		Application function		
Customer's Part Number	1		Monthly demand (pcs)		
		Spe	ecification		
		Spe	ecincation		
Number of Conductors			Total Length		mm
Pitch			Terminal Length		3mm
		0.50mm			4mm
		1.00mm			5mm
		1.25mm			6mm
		other ()			other ()
Conductor Width		0.30mm (0.50mm Pitch)	-Conductor thickness		35 µm
		0.60mm (1.00mm Pitch)			50 µm
		0.70mm (1.00mm Pitch)			100 µm
		0.80mm (1.25mm Pitch)			other ()
		other ()			Pb-Free, Non Halogen Free
		6mm	Insulation film (PET)		Halogen Free
Reinforcing (Supporting) tape		8mm			37 µm total thickness
		10mm		<u> </u>	43 µm total thickness
		15mm			50 µm total thickness
		other ()			60 µm total thickness
Shielding material		Aluminium foil			Whisker Controlled
		Copper foil	Product finishing		Au plating / Gold plating
		Silver foil			Impedance Controlled
		other (Whisker Free
Type S					☐ Insulation Film
Reinforcement tape at both ends		and the same and t			Conductor
of cable, on the same side		- B1			
		81			32
Type W	+			R2	
Reinforcement tape at both ends			ADDRESS.		Insulation Film
of cable, on the opposite side					Conductor Reinforce Tape
		B1 -			Remtorce tape
Type B	+				-
	_			15	Insulation Film
Single Reinforcement tape at one end and no Reinforcement					Conductor Reinforce Tape
		B1			nemote rape
tape at other end					
Type D					☐ Insulation Film
No Reinforcement tape					<u> </u>
•					Conductor
					Reinforce Tape
	1				
Remark:					
	_				
(€ [@] ∰ 	1	3 NET (13) DIV	UKRS (O) \$ (O) \$ (117	
REME			23 2	744	
			Copyrigh	t 2023© J	SB Tech Pte Ltd; All Rights Reserved